



TECHNICAL DATA
RR ENDURO 125 4T LC

CHASSIS

| | |
|-----------------------|---|
| Frame | steel double cradle frame |
| Wheel base | 1410 mm |
| Max length | 2115 mm |
| Max width | 820 mm |
| Max height | 1215 mm |
| Seat height | 925 mm |
| Ground clearance | 335 mm |
| Footrest height | 400 mm |
| Dry weight | 102 kg |
| Fuel tank capacity | 7,3 l. |
| Reserve | 1,5 l. |
| Front suspension | USD Hydraulic fork ø41 mm |
| Rear suspension | Monoshock with progressive compound lever |
| Shock absorber stroke | 131 mm |
| Front wheel travel | 260 mm |
| Rear wheel travel | 270 mm |
| Front brake | disc ø260 mm |
| Rear brake | disc ø220 mm |
| Front rim | 21 x 1,6 - 36 holes |
| Rear rim | 18 x 1,85 - 36 holes |
| Front tyre | 80/90-21 |
| Rear tyre | 110/80-18 |

ENGINE

| | |
|-----------------------|--|
| Type | Single-cylinder, 4-stroke, liquid cooled |
| Bore | 52,0 mm |
| Stroke | 58,6 mm |
| Displacement | 124,6 cc |
| Compression ratio | 11,2:1 |
| Ignition | Electronic 250W-14v |
| Spark plug | NGK CR8E |
| Lubrication | Forced with pump |
| Feeding | Unleaded gasoline |
| Carburettor | Keihin CVK 30 |
| Clutch | Wet multi-disc clutch |
| Transmission | 6 speed |
| Secondary trasmission | Z. 14/63 |
| Engine oil | SAE 15W/50 |